

# Trailer Suspensions



## 86AR SLIDER SUSPENSION

### TORQUE REQUIREMENTS

1. Tighten 3/4" or 7/8" u-bolt nuts	300-325 ft lbs	410-440 Nm
2. Tighten 7/8" torque arm and track rod nuts	400-425 ft lbs	545-580 Nm
3. Tighten 5/8" torque arm and track rod clamp nuts	125-150 ft lbs	170-205 Nm
4. Tighten 1/2" grade 8, air spring support nuts and track rod bracket	100-120 ft lbs	135-165 Nm
5. Tighten 7/8" grade 8, air spring support nuts	300-325 ft lbs	410-440 Nm
6. Tighten 3/4" shock absorber nuts	175-200 ft lbs	240-275 Nm
7. Tighten upper 1/2" air spring nuts	25-30 ft lbs	35-41 Nm
8. Tighten lower 3/8" air spring nuts	15-20 ft lbs	20-28 Nm
9. Tighten upper 3/4" air spring nuts	40-45 ft lbs	55-60 Nm
10. Tighten 1/4" air valve and linkage nut	5 ft lbs	7 Nm

ft lb = Foot - Pounds; Nm = Newton - Meters

**1-800-753-0050**  
[www.reycogranning.com](http://www.reycogranning.com)

Reyco Granning Suspensions  
1205 Industrial Park Drive  
Mount Vernon, MO 65712  
Phone: 417-466-2178  
Fax: 417-466-3964